REVISIONS				
LTR	DESCRIPTION	E.C.N.	DATE	BY/APPD
A	RELEASE TO DOCUMENT CONTROL	CB/085/99	08NOV1999	MRG
B	CHG HEATSINK DIM FR .252 TO .256, PKG DIM FR .320 TO .324, LD CUT FR .135 TO 1.47, ADD DIM (2.12); CHG TER 4 FR .51 TO (8.00), FR .315 TO (7.20); TOT LGH FR .520 TO .528; ADD DETAIL A; CHG LD THICK FR .236 TO .240; CHG FOOT LGTH FR .130 TO .150; ADD DIM (5.38); CHG LAND PATTERN DIM FR 9.50 TO 9.90 MIN, FR 9.00 TO 9.90 MIN, FR 4.00 TO 4.00 MIN, FR 1.50 TO 1.20 MIN; DEL NOTE C&D AND ARRANGE, ADD NOTE D.	CB/044/00	28FEB2000	MRG
C	CHG CEN LD CUT FR .135 TO 1.78 MAX; LD WID FR .026 TO .031; PKG THICK FR .220 TO .224; HEAT SINK THICK FR .145 TO .175; LD THICK FR .022 TO .025; FOOT LANDING FR .220 TO .224; FOOT ANGLE FR 2 TO 3 DEG; PROFILE DIM FR 0.13 MAX TO 0.25 MAX; BACK HEAT SINK WID FR (8.00) TO 6.22 MIN, LEN FR (7.20) TO 6.60 MIN; REMOVE EJECTOR PIN MARK; ADD NOTE E	CB/254/04	7OCT2004	RCM
D	REMOVE NOTE B; ADD NOTE E	CB/043/05	30MAR2005	MRG
5	REMOVED SITE INFO AND ECN COLUMN, ADDED NOTE F, TITLE CHANGED		06AUG2007	H.ALLEN
6	UPDATED HEATSINK PER IPC STANDARD, NOTE E IPC REFERENCE, FONT TO ARIAL, UPDATED DRAWING TITLE TO REFLECT JEDEC STANDARD.		02 MAY 09	H.ALLEN





LAND PATTERN RECOMMENDATION
UNLESS NOTED, ALL DIMS TYPICAL





NOTES: UNLESS OTHERWISE SPECIFIED
A) ALL DIMENSIONS ARE IN MILLIMETERS.
B) REFERENCE JEDEC, TO-263, VARIATION AB.
C) DIMENSIONING AND TOLERANCING PER ANSI Y14.5M - 1994.
D) LOCATION OF THE PIN HOLE MAY VARY (LOWER LEFT CORNER, LOWER CENTER AND CENTER OF THE PACKAGE).
E) LANDPATTERN RECOMMENDATION PER IPC TO254P1524X482-3N
F) FILENAME: TO263A02REV6



DETAIL A, ROTATED 90°
SCALE: 2X

APPROVALS	DATE
DRAWN: H.ALLEN	2 MAY 09
CHECKED: WB LEE	2 MAY 09
APPROVED:	

PROJECTION
INCH
[MM]

FAIRCHILD SEMICONDUCTOR™

2LD, JEDEC TO-263,VARIATION AB,SURFACE MOUNT

SCALE	SIZE	DRAWING NUMBER	REV
1:1	NA	MKT-TO263A02	6

FORMERLY: N/A
SHEET: 1 OF 1